












HEINE Binocular Loupes

	HR	HR-C	HRP	C
				
Magnification				
2x	<input type="checkbox"/>			
2.3x				<input type="checkbox"/>
2.5x	<input type="checkbox"/>	<input type="checkbox"/>		
3.5x			<input type="checkbox"/>	
4x			<input type="checkbox"/>	
6x			<input type="checkbox"/>	
Working distance				
250 mm (with close-up lenses)	<input type="checkbox"/>	--	--	--
340 mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
420 mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
450 mm	--	--	--	<input type="checkbox"/>
520 mm	<input type="checkbox"/>	<input type="checkbox"/>	--	--
Mounting options				
S-Frame 	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
Lightweight Headband 	--	<input type="checkbox"/>	--	<input type="checkbox"/>
Professional Headband 	<input type="checkbox"/>	--	<input type="checkbox"/>	--
Simple Metal Frame 	--	--	--	<input type="checkbox"/>
Accessories				
Close-up Lenses	<input type="checkbox"/> (for 340mm)	--	--	--
Protective Lenses	<input type="checkbox"/>	--	<input type="checkbox"/>	<input type="checkbox"/>
LED LoupeLight (Pages 125/126) 	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
Features				
i-View Function*	<input type="checkbox"/>	--	<input type="checkbox"/>	--
Modular	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
Water-resistant	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
Achromatic Optics	<input type="checkbox"/>	--	<input type="checkbox"/>	--
Optional Prescription Correction	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
Page	118/119	120	121	122

*i-View Function: Provides any angle of view and flips up the optics independently of the illumination beam of the LED LoupeLight.